

- Immersion type membrane filtration device has pneumatic pressure piping connected to air nozzle and treated water circulation piping being connected to lower portion of process tank.

L20 ANSWER 77 OF 121 WPINDEX COPYRIGHT 2002 DERWENT INFORMATION LTD

AN 2001-351320 [37] WPINDEX

DNC C2001-108618

DC D15

PA (MITO) MITSUBISHI JUKOGYO KK

CYC 1

PI JP 2001104760 A 20010417 (200137)\* 8p

ADT JP 2001104760 A JP 1999-283757 19991005

PRAI JP 1999-283757 19991005

AN 2001-351320 [37] WPINDEX

AB JP2001104760 A UPAB: 20010704

NOVELTY - An immersion type membrane device has several membrane filters (6) immersed vertically in treated water.

DETAILED DESCRIPTION - Several membrane filters (6) are immersed in treated water vertically. The pneumatic pressure piping (3) being connected to air nozzle (4) and treated water circulation piping (2) are connected to lower portion of process tank (1) containing treated water. The surface of **membrane** filters are **washed** by air bubbles from air nozzle. Both the pipings (2,3) are provided with regulating valves (11,12).

An INDEPENDENT CLAIM is also included for filter cleaning method.

USE - The device is useful for **cleaning membrane** filters.

ADVANTAGE - Improves **cleaning** effect of **membrane** filter as air bubble distribution and treated water flow rate are uniform. Facilitates adjustment of treat water **flow** rate and **air** bubbles. Improves rectifying action of **air** bubble **mixed** **water** as blow-off area of air bubbles in treated water is extended by providing a coarse mesh at bottom part of process tank.

DESCRIPTION OF DRAWING(S) - The figure shows the enlarged view of process tank lower part. (Drawing includes non-English language text).  
Process tank 1

Treated water circulation piping 2

Pneumatic pressure piping 3

Air nozzle 4

Membrane filter 6

Regulating valves 11,12

Dwg.2/7